FULLPOWER®

SLIDING TABLE SAW

SAW GUARD
Two types of saw guard for 90˚and 0˚ ~ 45˚ with easily replacement

MAIN SAW BLADE
Spindle of main saw is major axis rype, every axis is proofread its balance,and the rotation speed can be 3000/4000/5000/6000 rpm.



CROS CUT DIGITAL DISPLAY STOP
Cutting size can be read directly only on the digital display, which with micro-apparatus for accurate positioning. Max. cutting length 3000mm is available. (Opt.)



RIGID CROSS CUT TABLE
Highly steel structure of cross cut table is quickly locked to any of the sliding table.



MITRE FENCE
Reference position while 0˚~+/-45˚ degree scale for accurate degree reading and allow of angular cutting.

SLIDING TABLE SAW

ITEM / MODEL	STS-26TA	STS-32TA	STS-38TA
RECTIFIED CAST IRON FIXED TABLE DIMENSION	620*1000		
SLIDING TABLE DIMENSION	380*2600	380*3200	380*3800
MAIN SAW BLADE Φ305mm (12")	STANDARD		
MAIN SAW BLADE Φ355mm (14")/Max.	ADDITIONAL EXTRAS		
MAIN SAW BORE	Φ30 (Φ25.4)		
Max. CUTTING HEIGHT WITH BLADE AT 90°	100		
Max. CUTTING HEIGHT WITH BLADE AT 45°	70		
MAIN MOTOR POWER 7.5HP (5.5KW)	STANDARD		
MAIN MOTOR POWER 10HP (7.5KW)	ADDITIONAL EXTRAS		
MAIN BLADE SPEED	3000/4000/5000/6000RPM		
SCORING SAW BLADE Φ120	STANDARD		
SCORING SAW BLADE BORE	Φ22		
SCORING MOTOR POWER 1HP (0.75KW)	STANDARD		
SCORING BLADE SPEED 8000 RPM	STANDARD		
CUTTING WIDTH 1300mm	STANDARD		
CUTTING WIDTH 1500mm	ADDITIONAL EXTRAS		
CUTTING WIDTH ADJUSTMENT	MANUAL		
SAW TABLE EXTENSION 400mm	STANDARD		
SAWTABLE EXTENSION 800mm (CE)	ADDITIONAL EXTRAS		
MITRE FENCDE	STANDARD		
BLADE TILTING ADJUSTMENT	MANUAL(0°~45°)		
MAIN SAW HEIGHT ADJUSTMENT	MOTORIZE		
SCORING SAW HEIGHT ADJUSTMENT	MOTORIZE		
SCORING SAW +/- DIRECTION ADJUSTMENT	MOTORIZE		
BLADE TILTING ANGLE DIGITAL DISPLAY	STANDARD		
MAIN BLADE SPEED DIGITAL DISPLAY	STANDARD		
OVERHEAD SAW GUARD	LUXURIOUS (OPT.)		
CROSSCUT FENCE DIGITAL DISPLAY	ADDITIONAL EXTRAS		
RIP FENCE DIGITAL DISPLAY	ADDITIONAL EXTRAS		
RAPID CLAMP	ADDITIONAL EXTRAS		
TOOL FRAME	STANDARD		
DUST COLLECTION SYSTEM	MAIN CHANNEL 5", LUXURIOUS 3"		

* SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

FULLPOWER®

富堡實業有限公司
FULPOW INDUSTRIAL CORP.
7F-2, NO. 400, SEC. 1, CHANG PING ROAD, TAICHUNG, TAIWAN
TEL: 886-4-2243 9235 (REP.) FAX: 886-4-2244 3829
E-MAIL: fulpow@ms7.hinet.net